



BEDIENUNGSANLEITUNG

Lichtfunktionen

- 1 x Taste [ON] > 100% Leuchtleistung
- 2 x Taste [ON] > 50% Leuchtleistung
- 3 x Taste [ON] > 20% Leuchtleistung

Sonderfunktionen

- 1 x Taste [ON] gedrückt halten > Blinkmodus Intervall I 60 - 1000ms
- 1 x Taste [ON] kurz drücken > SOS internationales Notrufzeichen
- 2 x Taste [ON] kurz drücken > Blinkmodus Intervall 10ms

Ausschalten

- 1 x Taste [OFF] kurz > alle Funktionen ausschalten

LED Spannungsanzeige

- blaue LED > Spannung > 3.7 Volt
- grüne LED > Spannung 3.3 - 3.69 Volt
- rote LED > Spannung 2.9 - 3.39 Volt
- rote LED blinkt > Spannung < 2.9 Volt

Wartung und Lagerung

- Lagern Sie das Produkt sauber und in trockenem Zustand.
- Reinigen Sie die Lampe nach jedem Gebrauch mit Süßwasser. Nehmen Sie die Batterie aus der Lampe bei längerem Nichtgebrauch. Halten Sie den Li-Ion-Akku trocken und schmutzfrei.

Hinweise/Garantie

- Schauen Sie nicht direkt in das Licht und leuchten Sie nicht in die Augen anderer Person, da starke Beleuchtung die Augen schädigen kann.
- Vermeiden Sie, das Licht lange Zeit an Land zu verwenden und zu überhitzen, um die LED und die Leiterplatte nicht zu beschädigen.
- Öffnen Sie das Batteriegehäuse nicht unter Wasser, sonst werden die Batterie und die inneren Kreise beschädigt. Die Fehler fallen nicht unter Garantie.
- 2 Jahre Herstellergarantie. Bei Wassereintrich durch Bedienungsfehler oder unsachgemäße Handhabung erlischt die Garantie. Der Akku ist von der Garantie ausgeschlossen.

Spezifikationen

- Materialien T6061 Aluminium mit hartanodisierter Oberfläche
- Lichtquelle Cree Hochleistungs-LED-Chip Lebensdauer 50000 Stunden
- Lichtleistung 1000 Lumen
- Farbtemperatur 6000K - 6500K
- Abstrahlwinkel 9-12 Grad im zentrierten Strahlfleck
- Tiefe / wasserdicht bis 100m
- SS304-Knopfschalter mit Betriebsanzeigeleuchte
- Brennzeit ca. (100%) 90 min -(50%) 180 min (20%) 380 min
- Nettogewicht (g) 180g (ohne Batterie)
- Energietyp 1 x 18650 Li-Ion-Akku
- Die Atlantis Tauchlampe hat einen Überhitzungsschutz. Die Leistung wird ab 50° (automatisch auf ca. 17% Leuchtkraft reduziert um Schaden zu vermeiden. Ab 40° (steigt die Leuchtkraft wieder auf 100%.





OPERATION MANUAL

Light functions

- 1 x Button [ON] press short > 100% Lumisoity
- 2 x Button [ON] press short > 50% Lumisoity
- 3 x Button [ON] press short > 20% Lumisoity

Special functions

- 1 x Button [ON] press and hold > Flash on/Interval 60 - 1000ms
- 1 x Button [ON] press short > SOS International emergency sign
- 2 x Button [ON] press short > Flash on/Interval 10ms

Switch off

- 1 x Button [ON] press and hold > power of all functions

LED Power indicator

- blue LED > Voltage > 3.7 volts
- green LED > Voltage 3.3 - 3.69 volts
- red LED > Voltage 2.9 - 3.39 volts
- red LED flash > Voltage < 2.9 volts

Maintenance and storage

- Storage the product in a clean and dry condition.
- Clean the light in fresh water after each use. Take out the battery from housing if it is a long time not in use. Keep the Li-ion battery in dry and clean condition.

Warning and guarantee

- Do not directly look in the light or point direct to other person's eyes, high power lighting can damage eyes.
- Avoid using the light long time on the land and avoid overheating, which can damage LED, circuit board.
- Do not open the battery housing under the water, otherwise the battery and the inner circuits will be damaged. The faults will not be in the guarantee.
- 2 year manufacturer warranty. In case of water ingress through operating errors or improper handling, the guarantee is void. The battery and charger are excluded from the guarantee.

Specifications

- Materials T6061 aluminum with hard-anodized surface finish
- Light source Cree high intensity LED chip Life 50000 hrs.
- Light output 1000 Lumen Color
- Temperature 6000K - 6500K
- Pattern Angle 9-12 degrees in centered beam spot
- Deep rate up to 100m/300ft
- SS304 button switch with power indicator light
- Burning time (100 %) 90 min -(50%) 180 min -(20%) 380 min
- Net Weight (g) 180g (exclude battery)
- Power type 1 x 18650 Li-ion rechargeable battery
- The Atlantis torch has overheat-protection. It means the light will, in case of over 50° C inside of the light head, auto turn to low output of about 17% lighting. From 40° (the luminosity increases again to 100%.

