


# O<sub>2</sub> - Scuba Diving Sensor

## Type D-06



### KEY FEATURE

**Dual-cathode galvanic gas sensor with an extra water repellent head space.**

All characteristics are based on conditions at 25°C, 50% RH and 1013 hPa.

<b>Electrical Connector:</b>	gold-plated slip rings
<b>Measurement Range:</b>	0 to 100 Vol. %
<b>Sensor Lifetime:</b>	< 3 years @ ambient air
<b>Expected Operating Life:</b>	~ 500,000 Vol. % h
<b>Initial Output Signal:</b>	14.5 to 20.0 mV @ dry ambient air, 600 Ohm load
<b>Response Time t90:</b>	< 12 s
<b>Drift:</b>	< 1 % volume O <sub>2</sub> / month @ air, averaged across 12 months
<b>Linearity Error:</b>	< 3 % @ 100 % O <sub>2</sub> , applied for 5 min
<b>Output Differential:</b>	U <sub>1</sub> - U <sub>2</sub> < 10% < U <sub>1</sub> + U <sub>2</sub> @ 20 % to 100 % O <sub>2</sub>
<b>Zero Offset Voltage:</b>	< 200 µV in 100 % N <sub>2</sub> , applied for 5 min
<b>Operating Temperature:</b>	0 to 45 °C
<b>Pressure Range:</b>	600 to 1750 hPa
<b>Influence of Humidity:</b>	-0.03 % rel. O <sub>2</sub> reading per % RH
<b>Interferences:</b>	none to He, H <sub>2</sub> and CO
<b>Weight:</b>	approximately 20 g
<b>Material in Contact with Media:</b>	PA, PPS, PTFE, stainless steel

### STORAGE CONDITIONS

<b>Temperature Range:</b>	recommended: 5 to 30 °C maximum: -20 to 50 °C
<b>Ambient Pressure:</b>	600 to 1750 hPa
<b>Humidity:</b>	up to 100 % Rh
<b>Shelf Life:</b>	< 6 months recommended

### RELATED PRODUCTS

Product	Part-No.	Housing Colour
O <sub>2</sub> - Sensor D-06	41 00 56	white

[www.nrc-international.com](http://www.nrc-international.com)



**NRC International GmbH**

Stentenberg Str. 63  
D-51702 Bergneustadt

Phone +49(0)2261-500414  
Fax +49(0)2261-500415

[info@nrc-international.com](mailto:info@nrc-international.com)